




SAMMYS X-Press Vertical Mount



Patent No. 6,935,821

ROD SIZE	PART NUMBER	MODEL	DESCRIPTION	ULTIMATE PULLOUT (LBS)	UL LISTED	TEST LOAD (LBS)	FM APPROVED	TEST LOAD (LBS)	MIN THICK	MAX THICK	BOX QTY	CASE QTY	APPLICATION
1/4"	8181922	XP 200	X-Press 200	1146 (22 ga)	185 (Luminaire) 250 (Luminaire)				.027" .056"	.125"	25	125	Metal Deck
3/8"	8150922	XP 20	X-Press 20	1146 (22 ga)	850 (2½" Pipe) 185 (Luminaire) 250 (Luminaire) 283 (Conduit & Cable)		940 (2" Pipe) 1475 (4" Pipe)		.027" .056"	.125"	25	125	Metal Deck
3/8"	8153922	XP 35	X-Press 35	1783 (16 ga)	1250 (3½" Pipe) 85 (Luminaire) 250 (Luminaire) 416 (Conduit & Cable)		940 (2" Pipe) 1475 (4" Pipe)		.060" .105" .027" .056"	.125"	25	125	Purlin
3/8"	8150922	XP 20	Sammy X-Press 20	1146 (22 ga)	850 (2½" Pipe)		Pre-Pour Structural Concrete @ 3000 psi Post-Pour Range II LWC ≤ 35 PCF (lbs/ft³)				25	125	Metal Deck (Pre-Pour) Metal Deck (Post-Pour)




SAMMYS X-Press Swivel Head®



Patent Pending FOR EXTREME OR VARIANT ROOF PITCHES

ROD SIZE	PART NUMBER	MODEL	DESCRIPTION	ULTIMATE PULLOUT (LBS)	UL LISTED	TEST LOAD (LBS)	FM APPROVED	TEST LOAD (LBS)	MIN THICK	MAX THICK	BOX QTY	CASE QTY	APPLICATION
3/8"	8294922	SXP 20	Swivel X-Press 20	1061 (22 ga Vertical) 829 (45° Off Vertical)	750 (2" Pipe) 170 vertical (Luminaire) 80 @ 45° (Luminaire) 283 vertical (Conduit & Cable) 233 @ 45° (Conduit & Cable)		635 (2" Pipe)		.027"	.125"	25	125	Metal Deck
3/8"	8295922	SXP 35	Swivel X-Press 35	1675 (16 ga Vertical) 1558 (89° Off Vertical)	1500 (4" Pipe) 250 vertical (Luminaire) 80 @ 90° (Luminaire) 500 vertical (Conduit & Cable) 333 @ 89° (Conduit & Cable)		635 (2" Pipe)		.060"	.125"	25	125	Purlin
1/2"	8272957	SXP 2.0	Swivel X-Press 2.0	1061 (22 ga Vertical) 829 (45° Off Vertical)					.027"	.125"	25	125	Metal Deck
1/2"	8271957	SXP 3.5	Swivel X-Press 3.5	1675 (16 ga Vertical) 1558 (89° Off Vertical)					.060"	.125"	25	125	Purlin

SAMMYS X-Press Horizontal Mount



Patent Pending (SWXP)

ROD SIZE	PART NUMBER	MODEL	DESCRIPTION	ULTIMATE PULLOUT (LBS)	UL LISTED	TEST LOAD (LBS)	FM APPROVED	TEST LOAD (LBS)	MIN THICK	MAX THICK	BOX QTY	CASE QTY	APPLICATION
3/8"	8293957	SWXP 35	Sidewinder X-Press 35	1798 (16 ga)	1250 (3½" Pipe) 80 (Luminaire) 416 (Conduit & Cable)				.060"	.125"	25	125	Purlin