

## Sheet Steel Gauges

GAUGE NO.	26	24	22	20	18	16	14	12	3/16"	1/4"
Nominal Decimal Equivalent	.018	.024	.030	.036	.048	.060	.075	.105	.188	.250

## Ultimate Pullout Values (avg. lbs. ultimate) - SAMMYS

FASTENER			STEEL GAUGE (lbs.)						
MODEL	DIA.	PT	20	18	16	14	12	3/16	1/4
DST	1/4	#3	446	613	970	1145	1544	3190	-----
DST 516	5/16	#3	457	568	1209	1712	2422	-----	-----
TEK 50	#12	#5	-----	487	699	913	1527	3270	3593
DSTR 1-1/2"	#12	#5	-----	-----	-----	-----	-----	3270	3593
DSTR 1"	1/4	#3	1510	-----	-----	-----	-----	-----	-----
DSTR 516	5/16	#3	2200	-----	-----	-----	-----	-----	-----

## Aluminum Curtain Wall Extrusion Ultimate Pullout Values

(AVERAGE LBS. ULTIMATE)						
FASTENER			THICKNESS			
MODEL	DIA.	PT.	.114	.092	.365	.132
DST 10	1/4	#3	1265	-----	2750	-----
SWD 10	1/4	#3	-----	1120	-----	1420

## Ultimate Pullout Values (avg. lbs. ultimate) - SIDEWINDERS

FASTENER			STEEL GAUGE (lbs.)						
MODEL	DIA.	PT	20	18	16	14	12	3/16	1/4
SWD	1/4	#3	-----	-----	1477	-----	-----	-----	-----
SWDR 1-1/2"	#12	#5	2375	-----	-----	-----	-----	-----	-----
SWDR 1"	1/4	#3	1900	-----	-----	1900	-----	-----	-----
SWDR 516	5/16	#3	2480	-----	-----	2480	-----	-----	-----



Call our toll free number 800-387-9692 or visit [www.itwconstruction.ca](http://www.itwconstruction.ca) for general information.  
Visit ITW Buildex's SAMMYS web site [www.sammysuperscrew.com](http://www.sammysuperscrew.com) for the most current product and technical information.