

SELECTION CHART



■ Part # 8113910

Toggles

| ROD SIZE | PART NUMBER | MODEL | DESCRIPTION | ULTIMATE PULLOUT (LBS) | CASE QTY | NUT DRIVE |
|----------|-------------|--------|-------------|---|----------|----------------|
| 3/8" | 8064925 | SST 30 | 1/4 x 3" | 450 (Lath & Plaster) 404 (2 Layers 5/8 Rock) | 125 | Part # 8113910 |



Installation Tool
Part # 8110910

Ceiling Screws

| SUB-STRATE | PART NUMBER | MODEL | DESCRIPTION | ULTIMATE PULLOUT (LBS) | ICC TEST LOAD (LBS) | BOX QTY | CASE QTY |
|------------|-------------|---------|--------------|---------------------------|---------------------|---------|----------|
| STEEL | 8107957 | CWSD 1 | 1/4 x 1" | 472 (20 ga) | 170 (20 ga) | 25 | 125 |
| STEEL WOOD | 8190957 | CWSD 15 | 1/4 x 1-1/2" | 472 (20 ga) 1393 (Fir) | 170 (20 ga) | 25 | 125 |
| STEEL | 8108957 | CWSD 2 | 1/4 x 2" | 472 (20 ga) | 170 (20 ga) | 25 | 125 |

(Does not comply with ROHS requirements)

This confirmation, as evidenced in ICC-ES evaluation report ER-5367, provides guidance to code officials faced with approving the use of Sammy Ceiling Screws under these codes.